

WASTE STREAM	2D118	Plutonium Plants Initial/Interim Decommissioning: Processing Plants
--------------	-------	---

SITE Sellafield

SITE OWNER Nuclear Decommissioning Authority

WASTE CUSTODIAN Sellafield Ltd

WASTE TYPE ILW

WASTE VOLUMES

	Reported (m ³)	OR	Conditioned (m ³)	Packaged (m ³)
Stocks:	At 1.4.2025 = 0			
Future arisings:	1.4.2025 - 31.3.2044 = 0			
	1.4.2045 - 31.3.2048 = 9.5			
	1.4.2048 - 31.3.2059 = 46.2			
	1.4.2059 - 31.3.2063 = 6.6			
	1.4.2063 - 31.3.2065 = 8.0			
	1.4.2065 - 31.3.2073 = 21.5			
	1.4.2094 - 31.3.2104 = 26.4			
Total future arisings:	118.2			
Total waste volume:	118.2			

Number of waste packages in stock: At 1.4.2025..... - packages

Comment on arising rates: Arisings based on decommissioning programme.

Additional information on quantities: Waste within this waste stream is generated from a number of decommissioning projects which will commence at a future date. As a result of this, minimal characterisation of waste volumes and fingerprints has been carried out and hence there is a large uncertainty in the potential arisings. Preliminary assessments indicate that the volumes may vary from -30% to +200% for ILW.

Uncertainty factors on volumes: Stock (upper): x - Arisings (upper): x 3.00
Stock (lower): x - Arisings (lower): x 0.70

WASTE SOURCE Waste arises from the dismantling of plutonium processing plant.

PHYSICAL CHARACTERISTICS

General description: Plant and equipment, internal building fabric and soft waste i.e. rubber/PVC/paper. Most items size reduced in-situ. Some large items may be present.

Changes since waste generated: -

Bulk density (t/m³): ~ 0.50

Comment on density: Density stated is average for ILW and includes some voidage.

CHEMICAL COMPOSITION

General description and components (%wt): Stainless Steel 62.4%, Carbon/mild steel 36%, Copper 0.5%, Aluminium 0.5%, Lead 0.1%, Zinc 0.05%, Plastics 0.25%, Rubber 0.2%. Percentages by weight.

Chemical state: Neutral

Sheet metal proportion / thickness: Some sheet metal present (~30%), bulk metal (70%).

Metals and alloys (%wt):

	(%wt)	Type(s) / Grades(s) with proportions	% of total C14 activity
Stainless steel.....	= 62.4	The most commonly used stainless steel is 304L.	
Other ferrous metals.....	= 36.0	-	
Iron.....		-	
Aluminium.....	= 0.50	-	
Beryllium.....	= 0	-	
Cobalt.....	= 0	-	
Copper.....	= 0.50	-	
Lead.....	= 0.10	-	
Magnox/Magnesium.....	= 0	-	
Nickel.....	= 0	-	
Titanium.....		-	
Uranium.....	= 0	-	
Zinc.....	= 0.05	-	
Zircaloy/Zirconium.....	= 0	-	
Other metals.....	= 0	-	

Organics (%wt):

	(%wt)	Type(s) and comment	% of total C14 activity
Total cellulose...	= 0	-	
Paper, cotton...	= 0	-	
Wood...	= 0	-	
Halogenated plastics...	= 0.25	-	
Total non-halogenated plastics...	= 0	-	
Condensation polymers...	= 0	-	
Others...	= 0	-	
Organic ion exchange materials...	= 0	-	
Total rubber...	= 0.20	-	
Halogenated rubber...		-	
Non-halogenated rubber...		-	
Hydrocarbons...		-	
Oil or grease...		-	
Fuel...		-	
Asphalt/Tarmac (cont.coal tar)...		-	
Asphalt/Tarmac (no coal tar)...		-	
Bitumen...		-	
Others...		-	
Other organics...	= 0	-	

Other materials (%wt):

	(%wt)	Type(s) and comment	% of total C14 activity
Inorganic ion exchange materials...	= 0	-	
Inorganic sludges and flocs...	TR	-	
Soil...	= 0	-	
Brick/Stone/Rubble...	= 0	-	
Cementitious material...	= 0	-	
Sand...	TR	-	
Glass/Ceramics...		-	
Graphite...	= 0	-	
Desiccants/Catalysts...	= 0	-	
Asbestos...	TR	Due to the age of facilities covered by this waste stream trace amounts of white, blue and brown asbestos may be present.	
Non/low friable...		-	
Moderately friable...		-	
Highly friable...		-	
Free aqueous liquids...	= 0	-	
Free non-aqueous liquids...	= 0	-	
Powder/Ash...	= 0	-	

COMPONENTS OF MATERIALS, WASTE PROPERTIES, MATERIALS NOT CONTRIBUTING TO MASS

Inorganic anions (%wt):

	(%wt)	Type(s) and comment
Fluoride...	= 0	-
Chloride...	= 0	-
Iodide...	= 0	-
Cyanide...	= 0	-
Carbonate...	= 0	-
Nitrate...	= 0	-
Nitrite...	= 0	-
Phosphate...	= 0	-
Sulphate...	= 0	-
Sulphide...	= 0	-

Materials of interest for waste acceptance criteria:

	(%wt)	Type(s) and comment
Combustible metals...	= 0	-
Low flash point liquids...	= 0	-
Explosive materials...	= 0	-
Phosphorus...	= 0	-
Hydrides...	= 0	-
Biological etc. materials...	= 0	-
Biodegradable materials...	= 0	-
Putrescible wastes...	= 0	-
Non-putrescible wastes...	= 0	-
Corrosive materials...	= 0	-
Pyrophoric materials...	= 0	-
Generating toxic gases...	= 0	-
Reacting with water...	= 0	-
Higher activity particles...	NE	-
Soluble solids as bulk chemical compounds...	= 0	-

Hazardous substances / non hazardous pollutants:

	(%wt)	Type(s) and comment
Acrylamide.....	-	-
Benzene.....	-	-
Chlorinated solvents.....	-	-
Formaldehyde.....	-	-
Organometallics.....	-	-
Phenol.....	-	-
Styrene.....	-	-
Tri-butyl phosphate.....	-	-
Other organophosphates.....	-	-
Vinyl chloride.....	-	-
Arsenic.....	-	-
Barium.....	-	-
Boron.....	-	-
Boron (in Boral).....	-	-
Boron (non-Boral).....	-	-
Cadmium.....	-	-
Caesium.....	-	-
Selenium.....	-	-
Chromium.....	-	-
Molybdenum.....	-	-
Thallium.....	-	-
Tin.....	-	-
Vanadium.....	-	-
Mercury compounds.....	-	-
Others.....	-	-

Complexing agents (%wt):

No		
	(%wt)	Type(s) and comment
EDTA.....	-	-
DPTA.....	-	-
NTA.....	-	-
Polycarboxylic acids.....	-	-
Other organic complexants.....	-	-
Total complexing agents.....	= 0	-

Physical components:

	Number	Type(s) and comment
Sources.....	0	-
Electronic & Electrical Equipment (EEE)		
EEE Type 1.....	P	-
EEE Type 2.....	P	-
EEE Type 3.....	P	-
EEE Type 4.....	0	-
EEE Type 5.....	TR	-

TREATMENT, PACKAGING AND DISPOSAL

Planned on-site / off-site treatment(s):

Treatment	On-site / Off-site	Stream volume %
Size reduction	On-site	= 100.0
Decay storage		
Low force compaction		
Supercompaction (HFC)		
Incineration		
Drying/dewatering/liquid separation		
Tie down/fixatives/strippable coating/painting application		
Decontamination		
Metal treatment		
Recycling / reuse		
Thermal treatment, including vitrification		
Encapsulation		
Polymer encapsulation		
Other physical treatment		
Other chemical treatment		
Containerisation		
Treatment not yet determined		
None		

Comments on planned treatments:

-

Conditioning method:

All waste is planned to be flood grouted into DCCs.

Conditioning plants:

Plant Name	Location
Decommissioning Encapsulation Plants (DEP)	Sellafield

Likely conditioning matrix:

-

Further information on the conditioning matrix:

-

Waste Packaging:

Likely container type:	Container	Waste packaged (vol%)	Waste loading (m³)	Payload (m³)	Number of packages	Estimated start date for packaging
	DCC	100.0	0.37	1.5	324	-

Range in container waste loading: The volume of raw waste in a container can vary from 5% to 65% by volume (Note a full container of dry sharp sand would be 50% by volume).

Other information on packaging and conditioning: -

Conditioned density (t/m³): ~ 1.0

Conditioned density comment: Conditioned waste density varies depending on waste loading.

Management Routes:

Disposal Route	Stream volume %	Raw density t/m³	Start date
Expected to be consigned to a Near Site, Near Surface Disposal Facility (Scotland)	= 100.0		
Expected to be Non-NSD HAW managed under Scottish Government's policy			
Expected to be disposed to LLW Vaults NRS Dounreay			
Expected to be consigned to the Geological Disposal Facility			
Expected to be consigned to a Near Surface Disposal Facility			
Expected to be consigned to the LLW Repository			
Expected to be consigned to a Landfill Facility			
Expected to be disposed On-Site			
Expected to be managed by In-Situ Disposal			
Expected to be consigned to an Incineration Facility			
Expected to be consigned to a Metal Treatment Facility			
Expected to be Out of Scope			
Expected to be recycled / reused			
Disposal route not known			

Classification codes for waste expected to be consigned to a landfill facility:

Opportunities for alternative disposal routing: Yes

Baseline Management Route	Opportunity Management Route	Stream volume (%)	Opportunity Confidence	Comment
GDF	LLWR	~ 20.0	AMBER	There is potential for up to 20% of the waste to be diverted as LLW to LLWR. Note this waste would be consigned under 2D111.

RADIOACTIVITY

Source: The main sources of activity are actinides and fission products.

Uncertainty: Waste within this waste stream is generated from a number of decommissioning projects which will commence at a future date. The uncertainties quoted for each nuclide represent both the uncertainty in quantification without detailed sampling and the likely variation of nuclides in different buildings consigned wastes under this waste stream. It is exceptionally unlikely that all the waste included in this waste stream will have the same variation in nuclide fingerprint. Also activity levels will depend on degree of decontamination achieved.

Measurement of radioactivities: -

Chemical form of radionuclides:

- H-3: Not present in significant quantities.
- C-14: Not present in significant quantities.
- Cl-36: Not present in significant quantities.
- Se-79: Not present in significant quantities.
- Tc-99: Not present in significant quantities.
- I-129: Not present in significant quantities.
- Ra: Not present in significant quantities.
- Th: Not present in significant quantities.
- U: Not present in significant quantities.
- Np: Not present in significant quantities.
- Pu: -

WASTE STREAM		2D118		Plutonium Plants Initial/Interim Decommissioning: Processing Plants					
Nuclide	Mean radioactivity, TBq/m³				Nuclide	Mean radioactivity, TBq/m³			
	Waste at 1.4.2025	Bands and Code	Future Arisings	Bands and Code		Waste at 1.4.2025	Bands and Code	Future Arisings	Bands and Code
H 3				8	Gd 153				
Be 10				8	Ho 163				
C 14				8	Ho 166m				
Na 22					Tm 170				
Al 26					Tm 171				
Cl 36				8	Lu 174				
Ar 39					Lu 176				
Ar 42					Hf 178n				
K 40					Hf 182				
Ca 41				8	Pt 193				
Mn 53					Tl 204				
Mn 54				8	Pb 205				
Fe 55				8	Pb 210				8
Co 60				8	Bi 208				
Ni 59				8	Bi 210m				
Ni 63				8	Po 210				8
Zn 65				8	Ra 223				
Se 79				8	Ra 225				
Kr 81					Ra 226				8
Kr 85					Ra 228				
Rb 87					Ac 227				
Sr 90				8	Th 227				
Zr 93				8	Th 228				
Nb 91					Th 229				8
Nb 92					Th 230				8
Nb 93m				8	Th 232				8
Nb 94				8	Th 234				
Mo 93				8	Pa 231				8
Tc 97					Pa 233				
Tc 99				8	U 232				
Ru 106				8	U 233				8
Pd 107				8	U 234				8
Ag 108m				8	U 235				8
Ag 110m					U 236				8
Cd 109					U 238				8
Cd 113m					Np 237				8
Sn 119m					Pu 236				
Sn 121m				8	Pu 238			~ 5.25E-03	C C 2
Sn 123					Pu 239			~ 1.20E-02	C C 2
Sn 126				8	Pu 240			~ 1.20E-02	C C 2
Sb 125					Pu 241			~ 5.51E-01	C C 2
Sb 126					Pu 242			~ 6.35E-06	C C 2
Te 125m					Am 241			~ 1.35E-02	C C 2
Te 127m					Am 242m				8
I 129				8	Am 243				8
Cs 134				8	Cm 242				8
Cs 135				8	Cm 243				8
Cs 137				8	Cm 244				8
Ba 133					Cm 245				8
La 137					Cm 246				8
La 138					Cm 248				
Ce 144				8	Cf 249				
Pm 145					Cf 250				
Pm 147				8	Cf 251				
Sm 147					Cf 252				
Sm 151				8	Unsp a				8
Eu 152				8	Unsp b/g				8
Eu 154				8	Total a	0	*	4.28E-02	*
Eu 155				8	Total b/g	0	*	5.51E-01	*

Bands (Upper and Lower)

A a factor of 1.5
B a factor of 3
C a factor of 10
D a factor of 100
E a factor of 1000

Note: Bands quantify uncertainty in the mean radioactivity.

Code

1 Measured activity
2 Derived activity (best estimate)
3 Derived activity (upper limit)
4 Not present
5 Present but not significant
6 Likely to be present but not assessed
7 Present in significant quantities but not determined
8 Not expected to be present in significant quantity
* Total calculated from the 114 declared radionuclides